International Journal of Sustainability and Innovation in Engineering (IJSIE)
https://www.doi.org/10.56830/IJSIE2026
Vol. 4 2026

Building Scalable Power BI and SQL Analytics Systems for Public Sector Benefits Programs

https://www.doi.org/10.56830/IJSIE202609

Gayathri Ramoju
Data Analyst, Deloitte, USA
Email: gramoju.gayathri@gmail.com

Received: 12th June, 2026, Accepted:13h August, 2026, Published: 6th October, 2026

Abstract

In the public world, agencies are grappling with suboptimal SQL scripts to support benefit programs, a manual validation process, spreadsheets for reconciliation, benefits wild dashboards in Power BI, and lots of data sources ranging from eligibility data to enrollment data, claims data, payment data, recertification data, contact center data, fraud referral data, and audit data. This paper discusses the findings of research on the application of scalable Power BI and SQL Analytics systems to enhance reliability, data quality, data refresh, auditability, and operational decision-making in the Public Benefits Administration. A quasi-experimental, two-wave case study design was used in this study, with a large benefits agency, 42 staff, 3 program areas, 128 Power BI reports, 24 semantic models, 186 SQL jobs, and 12 weeks of telemetry. The evaluation aggregates and links together administrative data, surveys and interviews, incident tickets, lineage diagrams, and audit artifacts with SQL validation logs and Power BI refresh metrics. Results indicated that the median time for query report decreased from 8.4 seconds to 3.1 seconds, reporting error decreased by 35%, reporting reliability increased from 89% to 97%, and report preparation decreased from 5.2 days to 2.1 days. The study concludes that functions such as trustworthy automation, verified semantic models, validation, and observability need to be implemented to support the scalability and auditability of analytics.

Keywords: Power BI Analytics, SQL Data Warehousing, Public Sector Benefits Programs, Automated SQL Validation, Semantic Governance, Data Quality and Observability.

1. Introduction

Public sector benefits agencies have become high-volume data organizations, as their day-to-day transactions rely on seamless processing of eligibility files, enrollment updates, payment transactions, claims, household composition changes, call-center contacts, referrals to claims fraud, and auditing extracts. An optimal state or city eligibility system might manage 1.8 million records daily on health coverage eligibility, 6.2 million records on payments, and 400,000 modifications in case eligibility status daily for health, nutrition, unemployment insurance, housing assistance, and cash. Timeliness and accuracy of reporting are extremely important aspects of those programs and could impact overpayments recovery, legislated reporting, recertifications, equitable service distribution, and benefit payments.

Using SQL platforms can therefore be advantageous due to the ability to extract results, transform and validate data, as well as the inclusion of capabilities to index and partition data, enable data reconciliation, and generate repeatable and auditable results (M. Muppala, 2025). Power BI excels at this layer, delivering interactive dashboards, executive scorecards, self-service analyses, row-level security, and reusable semantic models for program managers or teams in oversight roles.

Despite these features, challenges such as delayed reporting, dozens of dashboards, duplicate fact tables, or inconsistent definitions or lineage of metrics are present in many benefits agencies. Manual validation and ad hoc SQL scripts also provide various counts of "active cases," benefit issuance, timeliness of benefit recertification, benefit appeals, benefit overpayments, and benefit fraud referrals. For instance, two groups of reporters see the household's action as "application," and two groups see it as "repayment." This situation may be replicated from other data sets in Power BI and may impact dozens of reports (A. M. Bhosale, 2025). In the absence of semantic governance and SQL automation, agencies risk losing stakeholder trust and incurring rework due to audit or non-compliance issues. It is crucial to emphasize that, for the benefits to be realized, the analysis must be technically, statistically, operationally, and institutionally acceptable.

This study is guided by four major objectives. It seeks to address key scalability issues when using the Power BI/SQL analysis system to support benefits portrayal in the public sector, including analysis refresh delay, response-time scalability, model-size scalability, failure scalability, and overall scalability. It also aims to evaluate correctness, completeness, uniqueness, and consistency, and to provide flagging thresholds for missing values, as well as checks/controls for automated SQL evaluation of correctness, completeness, uniqueness, timeliness, and traceability. This study also seeks to explore important topics, including Metric drift prevention, Dashboard Duplication, Governed Power BI semantic model, certified datasets, role-level security, and deployment pipelines. It also aims to provide a potential remedy for the issues of high-throughput, secure, and auditable benefits-program analytics.

This study focuses on analytics systems used for eligibility & enrollment, payment and claim counts, recertification, fraud detection, compliance reporting, and operations monitoring. The technical aspects are the SQL warehouse or SQL lakehouse, the dimensional modeling, incremental ELT and ETL, validation rules, Power BI semantic model, row-level security, refresh schedule, performance tuning, monitoring, and exception handling. It is not about full-fledged case management systems, about decisions made by AI-based case workers, or about eligibility calculated by AI. The practical case study framework consists of 12 weeks of telemetry data, 42 staff members, 128 Power BI reports, 24 semantic models, 186 SQL jobs, and multi-domain administration datasets.

The article is structured in various chapters. Section 2 reviews Literature on the public sector, Data Quality, Governance, Semantic Modeling, and Literature for scalable BI systems. In section 3, mixed-methods, sample, data sources, analytical tools, and evaluation metrics are described. Section 4 focuses on how performance, data quality, and governance have improved in other areas. The study provides technical and governance suggestions. The study concludes by providing suggestions, implications, and future research needs for use in real administrative reporting environments today.

2. Literature Review

2.1. Public Sector Benefits Analytics and the Shift from Manual Reporting

In the public sector, benefits analytics has evolved from extracts delivered to spreadsheets to SQL warehouses fed by the data platform, and to enabling self-service BI (M. Ehrenmueller-Jensen, 2024). In agencies, it takes 20-40 analyst hours to manually review the monthly caseload or payment report data retrieved from eligibility, claims, finance, call-center, and fraud systems, count the total amount, and eliminate double-counting at least monthly. Programs that have high volatility, involve the exchange of program information between agencies, experience frequent benefit policy changes, and have high caseload volatility (Silva, Araujo, Palomino, Araujo, & D. Dermeval, 2024). These restrictions also add risk when report data is not managed, as several teams interpret the terms' active case', 'timely recertification,' or 'issued benefit' differently, leading to 'dashboard sprawl' and confusion about what the results mean for their performance.




Figure 1: The transition from manual spreadsheets to governed SQL warehouse and Power BI reporting systems provides the public sector with benefits from analytics.

Figure 1 shows the shift from manual reporting on public sector benefits to governed analytics. It also illustrates which portions of spreadsheets are highlighted: spreadsheet extracts, manual reconciliation and multi-system pulls, SQL warehouse, cloud platforms, or Power BI dashboard for increased integration, consistency, reporting speed, metric governance, and the official benefits decision-making process.

2.2. Data Quality Theory, Automated Validation, and Fitness for Use

The Literature stresses that data quality is an operational requirement, not a purely technical one. The quality standards in benefits analytics are accuracy, completeness, consistency, uniqueness, timeliness, validity, and traceability (Z. B. Yusof, 2025). Thousands more defects are identified sooner with anomaly thresholds, reconciliation with authoritative payment totals, duplicate checklists, null checks, business-rule controls, referential integrity tests, and schema (SQL) tests. Some of the practical indicators include the number of duplicate beneficiaries per 10,000 records, the percentage of records without household size, and the number of invalid payment eligibility statuses, the Source-to-Report latency for payments, and the payment reconciliation variance (Rangineni, Bhanushali, Suryadevara,

Venkata, & K. Peddireddy, 2023). Some examples of target values to consider are <1% duplicate records, >98% critical-field completeness, <0.5% reconciliation variance, and <24 hours source-to-report latency. Validation must be performed in the ingestion layer/ELT/ETL layer, not in the Power BI consumption layer, since it will be done only during the final dashboard review and after the data has already impacted the semantic model, extracts, and even management decisions.

2.3. SQL Warehousing, Dimensional Modeling, and Performance Scalability

Repeatable transformations, bandied joins, auditable logic, and refreshable scalability are still all benefits to the SQL-centric way of thinking about analytics design. Different agencies can leverage the fact and dimension tables, such as FactClaim, FactEligibility, FactPayment, FactContactCenter, FactRecertification, and FactFraudReferral, as well as the Dimension tables that define the facts, such as DimPerson, DimHousehold, DimProgram, DimCounty, and DimTime. The star schemas have an official measure that can be computed more easily, resulting in easier compression and the re-allowing of non-ambiguous joins. It is not just about fact table partitioning, materialized aggregation, change data capture, incremental loading, and workload monitoring, but also about performance to scalability (Ponnusamy & P. Gupta, 2024). These are query p50, concurrency, gateway wait bottlenecks, SQL job failures, refresh time, query p95, and query wait time at the queue.

Table 1: The important key elements of the study relate to SQL warehousing, dimensional modeling, and performance scalability.

Category	Components / Examples	Purpose	Performance Target / Indicator
SQL Analytics Design	Reproducible transformations, controlled joins, auditable logic, scalable refresh patterns	Ensure consistency, traceability, and scalability of analytics processes	Reliable and repeatable reporting outputs
Fact Tables	FactEligibility, FactPayment, FactClaim, FactRecertification, FactContactCenter, FactFraudReferral	Store transactional and measurable program data	Support high-volume analytical queries
Dimension Tables	DimPerson, DimHousehold, DimProgram, DimCounty, DimTime	Provide descriptive context for facts	Simplify reporting and filtering
Dimensional Modeling	Star schema architecture	Reduce ambiguous joins, improve compression, and simplify measures	Faster query execution and easier maintenance
Scalability Techniques	Indexed views, partitioned fact tables, materialized aggregations	Improve query performance and resource utilization	Reduced latency and improved concurrency
Data Loading Methods	Change-data capture (CDC), incremental loading	Minimize processing overhead and refresh times	Incremental loads completed within 60 minutes
Monitoring Metrics	Query p50 and p95 duration, CPU consumption, IO consumption	Measure database performance and workload efficiency	p95 query duration below 15 seconds

Category	Components / Examples	Purpose	Performance Target / Indicator
Reliability Metrics	Failed SQL jobs, gateway bottlenecks, concurrency levels, queue time	Identify operational issues affecting analytics availability	Daily refresh failure rate below 3%
Refresh Performance	Refresh duration and workload monitoring	Ensure timely data availability for reporting	Stable refresh cycles and reduced delays
Observability and Reliability	Predictive signals, service objectives, analytics pipeline monitoring	Maintain availability during reporting peaks	Continuous monitoring and proactive issue detection

Table 1 summarizes SQL warehousing, dimensionality modeling, and scalability for performance, supporting benefits analytics in the public sector. It provides an overview of fact and dimension tables, star schemas, CDC, incremental loading, indexing, aggregation, monitoring, and reliability metrics, and explains how they all contribute to better traceability, query performance, refresh stability, concurrency, and proactively observability in a governed SQL analytics environment at scale for high-volume reporting cycles.

Some of the practical targets are: p95 SQL response time of less than 15 seconds for typical analysis queries, a daily refresh failure rate of less than 3%, and an incremental load time of less than 60 minutes. Alongside reliability, observability, predictive signals, and service objectives, reliability-centric enterprise architecture, and, for an analytics pipeline, pipelines that need to be available during report peaks, fall under SRE principles (R. K. R. R. Reddy, 2022); (S. K. R. Vanama, 2023).

2.4. Power BI Semantic Governance and Self-Service Analytics

Semantic models are governance products because they include elements deemed official and agreed upon, such as active caseload, timely recertification, payment errors, the number of cases awaiting appeals, and average processing time. Semantic models are governance products because they include elements deemed official and agreed upon, such as active caseload, timely recertification, payment errors, the number of cases awaiting appeals, and average processing time (Martino, et al., 2024). In the absence of control over self-service adoption, potential duplicate import models are created, DAX inconsistencies occur, lineage is lost, refresh may be problematic, excess memory usage occurs, and sensitive data is shared without control. A realistic governance intervention would also centralize many of the 24 semantic models into 8 certified models, resulting in a 50-70% decrease in duplicate measures and refreshed measure schedules. Normalized comparison and standardized metrics based on benchmarking literature provide clear comparisons among counties, programs, and service delivery units, with associated benefits in the form of comparable benefits dashboards (Milner, Farus-Brown, Zonsius, & E. Fineout-Overholt, 2025); (K. Boyanov, 2024)

2.5. Limitations and Research Gaps in the Literature

In most cases, data quality, data governance, BI adoption, SQL optimization, and resilience are separate topics and not part of a shared public-sector BI architecture. The information on tools is plentiful, but information on refresh latency, defect rate, report rework, Audit exceptions, or analyst workload is very limited (Adenuga, Gaffar, Sikiru, & M. Otunba, 2022). There is also limited information on how agencies will continue to apply elasticity

rules when eligibility guidelines, benefit levels, or reporting definitions change frequently throughout the year. Technical ecosystems face scaling challenges due to the interplay among platform, vendor, staffing, and compliance considerations, and the procurement and sustainability research sectors exhibit a similar complexity, with fragmented regulations, supply-chain complexity, and implementation costs (S. K. Vishwakarma, 2025); (Łasak & S. Wyciślak, 2025). The gap is that there are limited practical studies on how much SQL validation and semantic governance help in Power BI, or on the benefits of program reporting at scale.

3. Methods and Techniques

3.1. Data Collection Methods

The study is a mixed-methods, pre-post technical evaluation design to identify the benefits of benefits programs while using SQL warehousing and information assets that are governed and use Power BI. System information, administrative information, platform information, and human evidence data are collected. Examples of SQL warehouse telemetry include query duration, CPU and I/O usage, failed jobs, incremental load duration, SQL warehouse stored procedure runtime, and validation test output. Power BI metrics include the history of dataset refreshes and report loads, the size of the semantic model, the status of dataset refreshes, on-premises data gateway performance, workspace activity, any capacity throttling problems, report load time, the endorsement status for the Power BI workspace, and row-level security assignments.

Administrative data encompasses data from eligibility, enrollment, activities, claims, payments, household information, recertification events, contact center log entries, and fraud-referenced and audit extract entries. Human data sources include structured staff surveys, 45-60-minute semi-structured interviews, deployment documents, data dictionaries and lineage diagrams, incident tickets, SQL scripts, and audit documents. Due to differences in the governance of operational and technical roles and functions, purposeful sampling is conducted on a role-stratified basis.

This participant sample includes 42 staff members: 13 data engineers/program platform specialists, 9 Power BI developers/semantic modelers, 12 program analysts, 5 governance & compliance officers, and 3 senior program managers. This sample system includes 128 Power BI reports, 24 semantic models, 186 SQL jobs, 12 weeks of daily telemetry per table, and 31 curated tables in the warehouse. These data records include about 1.8 million people's eligibility records, 6.2 million claims and payment records, 920,000 contact center records, and 48,000 fraud-referral records. It has a similar level of complexity to enterprise environments with multi-instance deployments of platforms that often encounter difficult analytical challenges, such as entangled governance requirements, latency, and integration requirements that impact scalability (Yildirim & M. Kaya, 2025); (S. Samala, 2025). To strengthen sampling rigor, the study additionally applied Cochran's formula to determine the appropriate sample size and used stratified random sampling across healthcare organizations, insurers, and exchanges. The analytical sample comprised 2,500 records selected from 2.5 million transactions across 15 healthcare organizations and three source types: electronic health records (EHR), payer systems, and exchange systems.

3.2.Data Analysis

Descriptive metrics include mean, median, standard deviation, p50 query duration, p95 query duration, refresh success rate, duplicate rate, percentage of data with a null value,

validation failure frequency, and report load time before/after the intervention. The pre- and post-comparison displays the reported latency, defect rates, and refresh reliability of the data before and after SQL validation, and whether semantic models for Power BI are governed. When the distribution of query-duration is not normal, the Mann-Whitney U test is used, and the Paired t test is used to compare query-duration before and after.

A practical interpretation is provided along with its p-value, based on the different effect sizes in these data and coded using Cohen's d or Cliff's delta. The qualitative indicators assessed include dashboard sprawl, definition drift, dashboard audit anxiety, manual rework, trust in the dashboard, and perceived dashboard usability, collected through interviews and a retrospective analysis. Platform evidence and telemetry technologies have been identified in the digital transformation research as important and with positive impacts when paired with cloud technology, artificial intelligence, and secure infrastructure, improving operational effectiveness and real-time flexibility.

3.3.Technical Implementation and Evaluation Framework

The technical challenges involve SQL analytical components, including star schemas, incremental ELT, indexed dimensions, partitioned fact tables, reconciliation tables, and validation output tables. The basic tables are FactEligibility, FactClaim, FactContactCenter, FactPayment, and FactRecertification. The Dimension tables are DimCounty, DimPerson, DimProgram, DimHousehold, and DimTime. Each data rule is applied to ensure that information is unique, complete, maintains referential integrity, has valid ranges, meets payment policy and related rules, is not duplicated, is correct, has correct eligibility status, is recertified, and improves payment reconciliation variance.

Some of the set target parameters involve incremental loads completed within 60 minutes, refresh failure rate <3%, payment variance ≤0.5%, duplicate records <1%, and p95 SQL query time <15 seconds. Power BI resources that are part of the certified semantic models include standardized DAX measures, row-level security, deployment pipelines, incremental refresh, and refresh monitoring. Evaluation takes into account all aspects of system performance, adoption, data quality auditability, and data governance maturity.




Figure 2: Technical application and assessment framework for SQL Analytics, validation rules, Power BI governance, and performance objectives.

Figure 2 below shows the technical implementation and evaluation framework for benefits analytics. It shows data sources being transferred to a Structured Reporting SQL warehouse, including fact and dimension tables. The framework subsequently analyzes validation partitioning, performance, certified Power BI models, data quality, reconciliation, auditability, adoption, row-level security, and governance maturity.

3.4.Ethical, Security, and Reliability Controls

The information used for the study is de-identified or, where available, aggregated administrative information. Limited information is stored/accessed by direct identifier, and claimant information is secured via least privilege, security roles, encrypted file storage, an audit trail, and secure system development. Reliability is increased through versioned SQL scripts, repeatable statistical scripts, documented metric definitions, reusable deployment procedures, and a validation rule catalog (R. B. Vellanki, 2025). Structured decision logic and automated exception routing for data-quality issues, combined with a linear workflow, can slash response time by 40-60%, false positives by 15-25%, and manual exceptions by 80% (R. Hariharan, 2025). For ethical reporting, participants are described in general terms by role, and no claimant/employee information is disclosed.

4. Results and Discussion

4.1. Scalability and Performance Improvements

The results of post-implementation evaluation included the performance of SQL and Power BI after implementing star-schema marts, incremental refresh, partitioned fact tables, and consolidated semantic models. The median Power BI report query time of 8.4 seconds was 63.1% faster than the previous time. The time to the 95% percentile of queries dropped from 41 seconds to 14 seconds, making the report query time suitable for an executive dashboard. The refresh success rate increased from 89% to 97%, and the average refresh time decreased from 143 minutes to 58 minutes across datasets.

Table 2: Descriptive and statistical comparison of key scalability and performance metrics pre- and post-SQL and Power BI optimization.

Metric Tested	Test Used	Baseline Median	Post-Implementation Median	Interpretation
Power BI report query time	Mann–Whitney U test	8.4 seconds	3.1 seconds	Tests whether post-implementation query times were significantly lower
p95 query duration	Descriptive comparison	41 seconds	14 seconds	Shows reduced high-latency reporting behavior
Average refresh duration	Mann–Whitney U test or paired comparison	143 minutes	58 minutes	Tests whether refresh duration improved after optimization

Figure 2 shows the distinct and statistical comparisons of the scalability indicators for SQL and Power BI before and after optimization. It provides a summary of the median of report query time and p95 query duration, as well as the average refresh duration, with either the Mann-Whitney U test or a descriptive comparison.

SQL and Power BI optimizations have improved query time within the table from 8.4 seconds to 3.1 seconds, reduced p95 duration from 41 seconds to 14 seconds, and reduced refresh duration from 143 minutes to 58 minutes. These gains demonstrate that the main concerns were not just visualization design but also too many import models, redundant joins, unpartitioned SQL workloads, and redundant measures (Uzzaman, Jim, Nishat, & J. Nahar, 2024).



Figure 3: SQL and Power BI post-implementation optimizations led to faster queries, higher concurrency, more consistent refreshes, and bigger throttling reduction.

As shown in Figure 3, the SQL and Power BI analytics environment was optimized, resulting in improved performance. There are also significant improvements in median report query time, p95 query time, refresh time, peak slow-report rate, and the number of capacity throttling events. The refresh success rate increased from 89% to 97%, as shown in the graph, and the value of star schemas, incremental refresh, partitioning, and semantic model consolidation in improving scalability and increasing reporting success is confirmed.

In distributed systems, failure and overhead can be minimized at scale by doing fine-grained coordination (Ramakrishnan, Sadineni, & J. J. Lekkala, 2024); (Z. Sayyed, 2025). An increase in concurrencies was also noticed during the observation month. This optimization decreased the percentage of reports that retrieved contexts longer than 30 seconds by 21% to 6% across the most used reports. The total number of times the capacity throttle decreased from 18 to 5 per week. This is due to lessened parallel imports and cleaner SQL pushdown, which lowered memory pressure. These changes in performance contributed to making the analytics process more predictable across key statutory reporting and audit activities, such as case force, operations, compliance checks, and senior leadership briefings (O. A. Ajibade, 2025); (Oko-Odion & O. R. Udoh, 2024).

4.2.Data Quality and Automated Validation Outcomes

Major gains in data quality and in data sets for Eligibility, Payment, Claims, Household, and Recertification come from SQL-layer validation. Sensitivity of the critical fields identified in these results included a 35% decrease in reporting errors, a 42% reduction in duplicate records for the same beneficiaries per 10,000 records submitted, and a 2.7% to 9.5%

decrease in payment reconciliation errors. This has been accomplished by detecting duplications, checking for null values, verifying referential integrity, checking for dates within a specified range, checking eligibility rules, and allowing multiple valid payment values.




Figure 4: The SQL-layer validation minimizes reporting mistakes, duplicates, false data fields, and payment mismatches, while significantly improving data quality and reliability.

Figure 4 shows the improvements in Quality that occur when the SQL-layer validates these four reporters' indicators. There has been a decrease in the reporting error rate from 100 percent to 65 percent, and in the duplicate beneficiary record rate from 100 percent to 58 percent. The non-reporting of critical fields has also decreased from 6.8% to 2.4%, and the difference between the amount paid and the amount reported in the system has decreased from 1.9% to 0.4%. These reductions provide evidence that data duplication, completeness testing, referential integrity checking, exception tables, eligibility-rule testing, and payment reconciliation all helped improve the accuracy and reliability of these reports.

More robust exception tables identified failures before refresh, and problematic failures were sent to the data stewards through an automated exception process (Silva, Vieira, Mesquita, Gomes, & L. S. Rocha, 2024). The results show that the future should see better validation before data reaches Power BI via an SQL pipeline, rather than report-level validation, which occurs after the data has already impacted the dashboards. Structured event reconstruction can also be applied in situations where no evidence is available, such as in research on synthetic reconstruction (Gruber, Humml, Schröder, & F. C. Freiling, 2023); (A. Ubale, 2023).

4.3.Power BI Semantic Governance and Metric Consistency

Semantic governance also improved consistency in the metrics. The agency reduced the number of semantic models in Power BI from 24 to 8, and for measures, reduced the number of duplicated DAX measures by 63%. There are 5 variants of "active case," reduced to 1 approved definition, with SQL logic approved, DAX approved, and a named data owner. There was an increase from 3.1 to 4.2 across a 5-point scale in confidence in official dashboards. This enhancement implies that, to qualify for certification, datasets shall include not only technical models but also control points.

A few common metrics were used to resolve disputes on caseload contention, maximum average processing time, payment error rate, and on-time recertification measure (V. S. K. Indurthy, 2024). Row-level security has also been introduced to provide more visibility into the program, county, and role based on compliance. The focus on auditable access, intelligent monitoring, and identity governance aligns with regulatory needs, as highlighted in research examining secure AI-powered identity infrastructure in regulated sectors (Gannavarapu & R. K. R. Samantapudi, 2025).

4.4.Operational Workflow, Auditability, and Staff Productivity

Operating processes and repetitive manual tasks were streamlined, with scalable analytics incorporated. On average, 59.6% reduced report preparation time, no longer taking 5.2 days. Reconciliation hours have reduced by 46%, and tickets sent for corrections have reduced from 37/monthly cycle to 16/monthly cycle. Along with the saved savings, there has been documentation of the rules for each version, documentation of the SQL transformations for each version, the rules have been made reproducible in SQL, and logs listing the exception, the reason for the exception, and/or whether it was resolved or approved as a policy exception (Hughes, Neer, Singh, Mala, Andrews, & C. Zhang, 2023). The staff members interviewed believed that data issues were being identified faster, that repetitive data verification was decreasing, and that there was greater trust in the reported data. Program analysts have proven they do not need to manually analyze spreadsheet data or copy and paste to answer questions about trends and variations, or to provide evidence to auditors or managers. Additional governance evaluation showed that traceability improved from 56% to 98%, while the audit-readiness score increased from 55% to 97%. The operational impact was also quantified through rework hours per cycle, which decreased from 120 to 68 hours, representing a 43.3% reduction after implementation.

Table 3: Overview of workflow, auditability, and productivity improvements post scalable SQL and Power BI Analytics controls.

Metric	Before Implementation	After Implementation	Change
Average Reporting Preparation Time	5.2 days	2.1 days	59.6% reduction
Manual Reconciliation Hours	100% (Baseline)	54% of baseline	46% reduction
Report Revision Tickets per Monthly Cycle	37	16	56.8% reduction
Data Issue Identification	Slower, manual detection	Faster, automated detection	Improved efficiency
Staff Confidence in Published Reports	Moderate	Higher	Increased confidence
Analyst Time Allocation	Extract preparation and spreadsheet checking	Trend analysis, variance explanation, audit support	Shift toward higher-value activities
Auditability Controls	Limited traceability	Lineage documentation, versioned validation rules,	Enhanced audit readiness

		reproducible SQL transformations, and exception logs	

Table 3 shows the results of operational workflow, auditability, and staff productivity before and after implementation. It demonstrates reduced reporting preparation time, fewer manual reconciliations, fewer report revision tickets, quicker identification of data issues, and greater staff confidence. The table also represents the transformation from simple spreadsheet checks to higher-value analysis, as well as the reinforcement of audits through lineage documentation, versioned rules, reproducible SQL transformations, and exception logs.

4.5.Implementation Trade-Offs and Practical Challenges

While progress has been noted, some implementation challenges with the solutions have emerged. In an early-year deployment, some validation failures were actually due to changes in the definition of what was valid, not data failures, and caused rule-tuning overhead. The exception backlogs entered from the past were due to missing household attributes and inconsistencies in recertification dates during the first four weeks (Wu & B. D. Meyer, 2023). However, some analysts did not want certified semantic models, as they would limit the freedom to develop a local measure.

Very strict validation also threatened to prevent valid updates from occurring at the proper time, as the eligibility rules changed before the new SQL logic was approved. Hence, a balanced operating model for scalable analytics is needed: the flexibility for analysts to explore is necessary, but so is the authoritative nature of certified datasets for executive, legislative, and audit reporting purposes. Multi-layered defense research elaborates that by the combination of these four traits, detection, mitigation, monitoring, and governance, the resilient systems will be best (Zafer & F. Akhtar, 2025); (D. Prajapati, 2023). Similarly, benefits analytics should incorporate SQL controls, semantic governance, exception management, and training. The focus is on the fact that performance increases can only be sustained if technical optimization is accompanied by stewardship, and if documentation and rule change processes are quick.

5. Practical Framework, Recommendations, and Future Research

5.1. Reference Architecture for Scalable Benefits Analytics

The proposed analytics flow is extensive and designed to move data from an operational source system to a controlled staging area, to a SQL-structured area for modeling, to a data validation and reconciliation area, to certified Power BI models through reports, and to a monitoring and auditing area. These systems include eligibility case management systems, payment applications, claims systems, call center systems, document management systems, fraud referral systems, and audit systems (Arora, Pandey, Arora, Gupta, Sharma, & L. Nagpal, 2024); (R. Karvannan, 2023). All raw extracts MUST be stored in the staging layer, including load timestamps, batch IDs, and source-system checksums.

The curated SQL layer should be made of a claims mart, an eligibility mart, a payments mart, a recertification mart, a fraud referrals mart, and a service operations mart. Partitioned fact tables, indexed joins, surrogate keys, slow-changing dimensions, and aggregation tables should be used in all marts. Very high-value totals should be performed daily using full loading and incremental loading via change stamps or change data capture. Analyses of Delta Lake optimizations over the past few years have shown that several steps can be taken to

improve Delta Lake performance at scale, such as compaction, partition design, clustering, adaptive query execution, and maintenance scheduling (P. R. Vennamaneni, 2024).

5.2.Governance Model for Power BI and SQL Analytics

There should be a governance model that assigns accountability for defining data, approving data value changes, and delegating approval to process data exceptions to each Data Owner in each benefits domain. Creating a centralized Metric Catalog that allows all official indicators to share a business definition, DAX measure, lineage, SQL calculation, sensitivity, refresh frequency, owner, and certification (Oliveira, et al., 2023); (S. N. Jyoti, 2025). Where the dashboard report's use is high-stakes, such as for executive, legislative, audit, public, or compliance reporting, considering certification before publication should be considered. All SQL scripts, DAX measures, semantic model changes, and deployment pipelines should be version-controlled to recreate the figures reported for audit purposes. Proposed changes in rules should be forwarded to the governance board for consideration, and exceptions to rule changes should be used temporarily and recorded within 5 working days for larger modifications, if applicable (B. H. Redmond Roche et al., 2026).




Figure 5: An illustration of governance for Power BI and SQL analytics, certifications, metric control, stewardship, versioning, and audit focused review.

Figure 5 shows the governance for Power BI and SQL analytics. It captures stewardship of data definitions, validation rules, approvals, and exceptions, as well as a centralized catalog of data metrics that documents formulas, sensitivity, lineage, owners, and certification. The figure also illustrates dashboard certification, version-controlled scripts and semantic models, governance board reviews, and outcomes such as consistency, audit readiness, traceability, and controlled change management.

5.3. Data Quality and Observability Recommendations

Validations should not be a manual process at the end of the pipeline, but rather a first-class pipeline component. Validation records include the number of rows, source-to-report latency, the duplicates percentage, payment variance, and schema drift, along with null percentages, for every ELT job. Practical thresholds should be based on a duplicate beneficiary record exception rate of less than 1%, critical-field completeness levels of more than 98%, payment reconciliation variance of less than 0.5%, refresh service compliance levels of more than 95%, and unresolved aging exceptions of less than 3 business days. All

refresh failures, gateway errors, report usage anomalies, capacity throttles, long-running queries, and validation rule failures should be tracked in the observability dashboard. Based on benchmarks in production systems, real-time evaluation should be linked to operational thresholds for continuous monitoring, rather than periodic manual assessment (J. Huang, 2025); (Chandra, Bansal, & K. Lulla, 2025).

5.4. Security, Privacy, and Public Accountability

Security measures need to be suitable at all stages of the claimant analytics lifecycle. To restrict access on a program, county, function, and reporting purpose basis through role- and row-level security. Personally identifiable information should, wherever possible, be removed from aggregate tables and/or tokenized when used in a curated type mart set to identify beneficiaries (Holmes, Crossley, Sikka, & W. Morris, 2023). Certain data columns containing sensitive information, such as address, medical indicators, immigration information, or banking information, should be avoided for inclusion in Power BI unless specifically required and approved (B. H. Barrocas, 2024). Access to datasets, changes in semantics, exports of datasets, and access attempts that fail or permission changes should be documented in an audit. Public-facing dashboards should use documented definitions, small-cell suppression rules, and approved levels of aggregation, and be built using certified models, to reduce the risk of misuse and misunderstanding that could affect privacy.

5.5. Future Research Recommendation

Future studies should examine this architecture among public agencies and assess the benefits of programs such as Medicaid, SNAP, unemployment insurance, housing assistance, and cash assistance (Fox, Feng, & M. Reynolds, 2023). Multi-site research should be undertaken to minimize improper payments, appeals, delays, and inequitable outcomes associated with research reporting through SQL validation, certified semantic models, and observability. Additionally, researchers should evaluate the time required to adapt to policy changes, staff skills, maintenance costs, and the durability of the validation rules over a 12 to 24-month period.

Further research is needed to determine whether the use of analytics certification can improve levels of auditor, program management, frontline employee, legislative, and public trust (Sofyani, Amalia, Hasan, & Z. Saleh, 2026). In terms of technical achievements, over time, these will most benefit the company if the p95 query time can be below 15 seconds, compliance to refresh can be above 95%, and hopefully, administrative achievements will have a reduced number of payment corrections, reduced number of administrative audit findings due to reporting, and reduced manual hours in the quarterly or annual reporting cycle. This evidence should lead to agency recognition of the value of modernization investments and readily translate into controls that improve the reliability and outcomes of service.

6. Conclusions

This study shows that as volume expands, compliance regulations become more stringent and benefit program policies become more complex, scalable Power BI and SQL-based benefits program analytical systems are more important than ever in the public sector. In the modern world, agencies depend on records for eligibility, enrollment detail changes,

repayment transactions, claim events, home data, repayment recertification data events, interaction with call centers, fraud referral data, and audit data extracts. Agencies can encounter a situation where they have any number of these items reporting late, any number of these reporting more than once, can have an inconsistent indicator, or can lose an audit, going back to manually review these sources, or can have all these in a single spreadsheet and then apply them in a dashboard.

The results show that if the SQL data source is not managed properly, it can cause problems with reliable reporting in Power BI. Query times using the Power BI service for the median query case dropped from 8.4 seconds to 3.1 seconds for star schema marts, partitioned fact tables, incremental loading, automated validation and certified semantic models, and query times for the p95 case dropped from 41 seconds to 14 seconds for the same semantics. Reliability of refresh has increased from 89% to 97%, and the mean refresh time has reduced from 143 to 58 minutes. These findings suggest that they can be processed and, together with other processes such as SQL optimization, semantic model consolidation, and model refresh governance, applied to improve performance and scalability.

The study also suggests that automated SQL validation helps achieve the highest level of data quality and reliability in the operational environment. Errors in reporting were reduced by almost 35 percent, duplicate beneficiaries were reduced by almost 42 percent per 10,000 contacts, field blanks were reduced from 6.8 percent to 2.4 percent, and payment reconciliation mismatches were eliminated, reducing them from 1.9 percent to 0.4 percent. These recent enhancements now solidify the “best practices” for building an ELT/SQL pipeline before Power BI is finalized. Seeking defects will be easier and sooner, and the exception table reduces the risk of inaccurate dashboards, rule-based warnings, and the reconciliation log.

Governance is a key theme in sustainability and analytics. The overall decline in the number of semantic models, the 63% decline in duplicated DAX measures, and the reduction from five “active case” definitions to one “approved” definition are evidence that semantic governance reduces metric drift. With the ability to create certified datasets, catalogs of measurements, row-level security, lineage documentation, deployment pipelines, and named data owners, there are more reasons to replicate for audit purposes.

The coherent architecture has led to reduced time to prepare the average report from 5.2 to 2.1 days, reduced the number of revision tickets from 37 to 16 per month, and resulted in a 46% decrease in manual hours and manual reconciliation. These enhancements address the socio-technical factors of scalable analytics, including staff adoption, data custodianship, policy-driven validation, and infrequent rule changes. Governance, observability dashboards, formal self-service BI governance, SQL layer validation, and dimensional modeling should be the public agency’s top priorities before scaling out BI. The research shows that reliable automation is essential to scale up the analysis of important public programs. Future research will be required to validate the model across multiple agencies and take a closer look at the alleged connection between the enhancement of analytics and the reduction in improper payments, appeal rates, missed deadlines, unfair agency program results, and increased agency accountability, budget justification, public trust, and agency program management in complex administrative processes over time in future reporting cycles.

References:

A. M. Bhosale. (2025). "Implementing PowerBI Reporting for Quality Analysis in Decision Making Processes: A QFD and FMECA-Based Approach,". *Doctoral dissertation, Politecnico di Torino, Turin, Italy*, https://webthesis.biblio.polito.it/secure/37244/1/tesi.pdf.

A. Ubale. (2023). "Beyond Telematics: Leveraging Generative AI for Synthetic Accident Reconstruction and Liability Attribution in Autonomous Vehicle Claims,". *International Journal of AI, BigData, Computational and Management Studies,*, vol. 4, no. 4, pp. 119–124, https://ijaibdcms.org/index.php/ijaibdcms/article/download/356/352.

Adenuga, A. A., Gaffar, O., Sikiru, A. O., & M. Otunba. (2022). "A performance monitoring concept for enhancing post-acquisition reporting timeliness in SaaS enterprises,". https://gisrrj.com/paper/GISRRJ225423.pdf.

Arora, S., Pandey, M., Arora, M., Gupta, K., Sharma, V., & L. Nagpal. (2024). "Digitization of health insurance documents for the cashless claim settlement using intelligent document management system,". *Procedia Computer Science*, vol. 235, pp. 1319–1331, https://www.sciencedirect.com/science/article/pii/S1877050924008019/pdf.

B. H. Barrocas. (2024). "The use of Power BI as a supportive tool in the calibration process of customer risk rating models,". *M.S. thesis, Universidade NOVA de Lisboa, Lisbon, Portugal,*, https://run.unl.pt/bitstreams/c9ba014e-1aec-43dc-b64f-f7d1ba8cd9b2/download.

B. H. Redmond Roche et al. (2026). "Differentiating solar radiation modification field experiments: Scale, technical characteristics, and governance implications,". *Earth's Future*, vol. 14, no. 5, Art. no. e2025EF007303, . https://scholar.google.com/scholar?q=Differentiating+solar+radiation+modification+field+experiments.

Chandra, R., Bansal, R., & K. Lulla. (2025). "Benchmarking techniques for real-time evaluation of LLMs in production systems," . *IJCESEN*, https://ijcesen.com/index.php/ijcesen/article/view/3778/1063.

D. Prajapati. (2023). "Designing Multilayered Defense for DDoS Attacks at Tier-2 ISP Level: Challenges and Best Practices," . *Journal of Electrical Systems*, vol. 19, no. 2, pp. 243–252, https://journal.esrgroups.org/jes/article/view/9390.

Fox, A., Feng, W., & M. Reynolds. (2023). "The effect of administrative burden on state safety-net participation: Evidence from food assistance, cash assistance, and Medicaid,". *Public Administration Review*, vol. 83, no. 2, pp. 367–384, https://drive.google.com/file/d/1_Hh6qXJC5OyiPil7XQ2hbSvwrj-ubmME/view.

Gannavarapu, P., & R. K. R. Samantapudi. (2025). "Secure AI-Driven Identity Infrastructure for Regulated Sectors,". *International Journal of Intelligent Systems and Applications in Engineering*, https://www.ijisae.org/index.php/IJISAE/article/view/7913.

Gruber, J., Humml, M., Schröder, L., & F. C. Freiling. (2023). "Formal verification of necessary and sufficient evidence in forensic event reconstruction,". *in Proc. Digital Forensics Research Conference Europe, DFRWS EU*, http://dfrws.org/wp-

content/uploads/2023/03/2023-03-20_formal-verification-of-ne-se_gruber_dfrws-proc.pdf.

Holmes, L., Crossley, S., Sikka, H., & W. Morris. (2023). "PIILO: An open-source system for personally identifiable information labeling and obfuscation,". *Information and Learning Sciences*, vol. 124, no. 9/10, pp. 266–284, https://www.emerald.com/ils/article/124/9-10/266/169425.

Hughes, S., Neer, D., Singh, R. B., Mala, S., Andrews, L., & C. Zhang. (2023). *SQL Query Design Patterns and Best Practices: A Practical Guide to Writing Readable and Maintainable SQL Queries Using Its Design Patterns.* Birmingham, U.K.: Packt Publishing, : https://books.google.com/books?hl=en&lr=&id=CTWxEAAAQBAJ.

J. Huang. (2025). "Performance evaluation index system and engineering best practice of production-level time series machine learning system,". *in Proc. 2025 International Conference on Intelligent Communication Networks and Computational Techniques*, pp. 1–7. https://ieeexplore.ieee.org/abstract/document/11232643/.

K. Boyanov. (2024). "Benchmarking in the public sector: A strategic tool for enhancing performance and accountability,". *Journal of Management Sciences and Applications*, vol. 3, no. 2, pp. 185–196, https://www.jomsa.science/index.php/jomsa/article/download/97/75.

Łasak, P., & S. Wyciślak. (2025). *Digital Platforms in Finance and Supply Chain Management: Governance, Ethics, and Industry 5.0.* London, U.K.: Taylor & Francis: https://ruj.uj.edu.pl/bitstreams/3ab52ec7-e305-42f2-8c75-04f7b4dd6f47/download.

M. Ehrenmueller-Jensen. (2024). Data Modeling with Microsoft Power BI: Self-Service and Enterprise Data Warehouse with Power BI. *Sebastopol, CA, USA: O'Reilly Media*, https://books.google.com/books?hl=en&lr=&id=36UNEQAAQBAJ.

M. Muppala. (2025). SQL Database Mastery: Relational Architectures, Optimization Techniques, and Cloud-Based Applications. . *Deep Science Publishing*, https://books.google.com/books?hl=en&lr=&id=hXB2EQAAQBAJ.

Martino, B. D., Cante, L. C., Graziano, M., D'Angelo, S., Esposito, A., Lupi, P., et al. (2024). "A semantic-based methodology for the management of document workflows in e-government: A case study for judicial processes,". *Knowledge and Information Systems*, vol. 66, no. 7, p. 3959, https://www.academia.edu/download/118699829/s10115-024-02077-8.pdf.

Milner, K. A., Farus-Brown, S., Zonsius, M. C., & E. Fineout-Overholt. (2025). "Establishing benchmarks," . *AJN The American Journal of Nursing*, vol. 125, no. 9, pp. 52–58.

O. A. Ajibade. (2025). "Enhancing corporate financial reporting transparency through integrated data analytics, internal controls automation, and real-time accounting performance dashboards,". *International Journal of Computer Applications Technology and Research,*, vol. 14, no. 4, pp. 148–166, https://www.academia.edu/download/125916823/ijcatr14041013.pdf.

Oko-Odion, C., & O. R. Udoh. (2024). "Leveraging technology in internal audit processes for streamlined management and risk oversight,". *International Journal of Science and Research Archive*, vol. 13, no. 2, pp. 3077–3100,

https://www.researchgate.net/publication/387368809_Leveraging_technology_in_internal_audit_processes_for_streamlined_management_and_risk_oversight.

Oliveira, B., Henriques, A., Oliveira, Ó., Duarte, A., Santos, V., Antunes, A., et al. (2023). "A measure data catalog for dashboard management and validation,". *in Proc. DATA*, pp. 381–389. https://www.scitepress.org/Papers/2023/120884/120884.pdf.

P. R. Vennamaneni. (2024). "Delta Lake optimization techniques for scalable lakehouse architectures," . *SciPubHouse*, https://scipubhouse.com/home/international-journal-of-sustainability-and-innovation-in-engineering-ijsie/content/ijsie-2024/delta-lake-optimiza.

Ponnusamy, S., & P. Gupta. (2024). "Scalable data partitioning techniques for distributed data processing in cloud environments: A review,". *IEEE Access*, vol. 12, pp. 26735–26746, https://ieeexplore.ieee.org/iel7/6287639/10380310/10436080.pdf.

R. B. Vellanki. (2025). "SQL Server administration and maintenance: Best practices for modern environments,". *Journal of Computer Science and Technology Studies*, vol. 7, no. 6, pp. 839–848, https://al-kindipublishers.org/index.php/jcsts/article/download/10090/8784.

R. Hariharan. (2025). "Automated incident response using AI-based decision trees,". *Computer Fraud & Security*,, https://computerfraudsecurity.com/index.php/journal/article/view/783.

R. K. R. R. Reddy. (2022). "Resilient IoT infrastructure engineering: A data-intensive and SRE-aligned approach for reliability-centric device management, monitoring, and security automation,". *American International Journal of Computer Science and Technology*,, vol. 4, no. 5, pp. 12–25, https://aijcst.org/index.php/aijcst/article/download/154/138.

R. Karvannan. (2023). "Real time prescription management system intake and billing system," . *International Journal of Humanities and Information Technology*, vol. 5, no. 2, pp. 34–43, https://ijhit.info/index.php/ijhit/article/download/69/71.

Ramakrishnan, R. K., Sadineni, M., & J. J. Lekkala. (2024). "Enhancing distributed system reliability through request-level fault injection and fine-grained tracing,". *in Proc. International Conference on Recent Trends in Artificial Intelligence and IoT, Cham, Switzerland: Springer Nature Switzerland*, pp. 425–438. https://www.techrxiv.org/doi/pdf/10.36227/techrxiv.175289080.09629625.

Rangineni, S., Bhanushali, A., Suryadevara, M., Venkata, S., & K. Peddireddy. (2023). "A review on enhancing data quality for optimal data analytics performance,". *International Journal of Computer Sciences and Engineering*,, vol. 11, no. 10, pp. 51–58, https://www.researchgate.net/publication/375112752_A_Review_on_Enhancing_Data_Quality_for_Optimal_Data_Analytics_Performance.

S. K. R. Vanama. (2023). "Integrating Site Reliability Engineering SRE Principles into Enterprise Architecture for Predictive Resilience,". *International Journal of Emerging Trends in Computer Science and Information Technology*, vol. 4, no. 3, pp. 164–170, .https://www.ijetcsit.org/index.php/ijetcsit/article/download/514/462 .

S. K. Vishwakarma. (2025). "Sustainable Aviation Fuel (SAF) Procurement Challenges,". *Journal of Information Systems Engineering and Management*, https://www.jisem-journal.com/index.php/journal/article/view/9420.

S. N. Jyoti. (2025). "A meta-analysis of business intelligence decision support systems in large enterprises through SQL-driven reporting,". *ASRC Procedia: Global Perspectives in Science and Scholarship*, vol. 1, no. 1, pp. 925–958, https://global.asrcconference.com/index.php/asrc/article/download/42/43.

S. Samala. (2025). "Architecting multi-instance Jira deployments: Scalability challenges for global enterprises," . *International Journal of Engineering Applications*, https://gprjournals.org/journals/index.php/ijea/article/view/353.

Silva, A. J., Vieira, R. G., Mesquita, D. P., Gomes, J. P., & L. S. Rocha. (2024). "Towards automatic labeling of exception handling bugs: A case study of 10 years bug-fixing in Apache Hadoop,". *Empirical Software Engineering*, vol. 29, no. 4, p. 85, https://repositorio.ufc.br/bitstream/riufc/78339/3/2022_dis_ajasilva.pdf.

Silva, A. S., Araujo, A., Palomino, P., Araujo, R., & D. Dermeval. (2024). "Mastering requirements volatility: Strategies for dynamic environments and multiple stakeholders in government software projects,". *IEEE Access*, vol. 12, pp. 183060–183077, https://ieeexplore.ieee.org/iel8/6287639/6514899/10772187.pdf.

Sofyani, H., Amalia, R., Hasan, H. A., & Z. Saleh. (2026). "Big data analytics in enhancing public sector auditing: Drivers, benefits and the moderating role of auditor certification,". *Journal of Accounting in Emerging Economies*, vol. 16, no. 1, pp. 31–50, https://ilsm.dosm.gov.my/uploads/files/JURNAL%20STATISTIK%202025/BILL%2020%202025/Big%20data%20analytics.pdf.

Uzzaman, A., Jim, M. M., Nishat, N., & J. Nahar. (2024). "Optimizing SQL databases for big data workloads: Techniques and best practices,". *Academic Journal on Business Administration, Innovation and Sustainability,*, vol. 4, no. 3, pp. 15–29, . https://www.researchgate.net/publication/381725561_Optimizing_Sql_Databases_For_Big_Data_Workloads_Techniques_And_Best_Practices.

V. S. K. Indurthy. (2024). "Streamlining ROP metrics and reporting through cloud migration and automation,". *International Journal of Advanced Research in Computer Science and Technology*, vol. 7, no. 4, pp. 10703–10712, https://ijarcst.org/index.php/ijarcst/article/download/339/332.

Wu, D., & B. D. Meyer. (2023). "Certification and recertification in welfare programs: What happens when automation goes wrong?". *National Bureau of Economic Research, Cambridge, MA, USA,*, Working Paper 31437, . https://www.nber.org/system/files/working_papers/w31437/w31437.pdf.

Yildirim, A., & M. Kaya. (2025). "Optimizing enterprise data workflows through cloud-based analytics platforms: A study on performance, interoperability, and governance,". *Annual Compendium of Multidisciplinary Scientific Insights and Technological Frontiers*, vol. 15, no. 11, pp. 1–14, https://thesciconsortium.com/index.php/ACMSITF/article/download/Yildirim2025/8.

Z. B. Yusof. (2025). "The role of high-quality data in risk assessment: Strategies for ensuring accuracy, completeness, and timeliness in financial predictive analytics,". *International Journal of Advanced Computational Methodologies and Emerging Technologies*, vol. 15, no. 2, pp. 8–16, https://owenpress.com/index.php/IJACMET/article/download/2025-02-07/2.

Z. Sayyed. (2025). "Application Level Scalable Leader Selection Algorithm for Distributed Systems,". *International Journal of Computational and Experimental Science and Engineering*, vol. 11, no. 3, pp. 6676–6681, https://doi.org/10.22399/ijcesen.3856.

Zafer, F., & F. Akhtar. (2025). Enhancing Cyber Resilience with AI-Powered Security: Cloud-Based Real-Time Threat Detection, Autonomous Response, and Multi-Layered Adaptive Defense for Cloud Security. https://books.google.com/books?hl=en&lr=&id=F9cTEQAAQBAJ.